$3M^{\text{TM}}$ Marine Adhesive Sealant Solutions For the Boat Owner

Come sun wind or high water



3M[™] Marine Adhesive Sealant Fast Cure 4000 UV

- A high performance, color-stable adhesive sealant that can be removed if rework or repair is necessary
- Flexibility helps dissipate stress caused by shock, vibration, swelling or shrinking
- Ideal for installing thru-hull fittings and deck hardware where a durable seal is required and where cosmetics are important, both above and below the waterline





3M[™] Marine Adhesive Sealant Fast Cure 4200

- Medium-strength adhesive allows for disassembly of parts after prolonged use
- Forms watertight, weather-resistant seals on hardware and in joints both above and below the waterline

3M[™] Marine Grade Silicone Sealant

- High quality silicone designed for harsh marine environments
- Mildew resistant
- Non-yellowing
- Remains flexible even after years of exposure

Vate

The toughest sealants on the sea

Whether you're bonding trim, toe rails, fittings or fiberglass deck components, or sealing thru-hulls, hatches, hinges, trunk joints or almost anything else on a marine vessel, 3M has an adhesive sealant that's proven to the task. Our products have set the standard for marine excellence for more than 50 years, and they now include a new generation of advanced polyurethane and silane-modified polymers (SMPs) that further expand their range and effectiveness.

3M[™] Marine Adhesive Sealants are specifically designed for the rigors of the marine environment, bonding or sealing everything from wood, metal and glass to gelcoat and most plastics-including fiber-reinforced plastic (FRP). Boaters have no better friend on the water.

3M[™] Marine Adhesive Sealant 3000 UV

- A single-component, elastomeric sealant that cures without isocyanates
- Excellent cosmetic sealant; will not degrade when exposed to UV
- Low VOC, 50-minute skin time, paintable when wet
- Ideal for port hole and general cosmetic seam sealing

3M[™] Marine Adhesive Sealant 5200

- An exceptionally strong, high performance polyurethane
- Creates extremely strong bonds, above and below the waterline
- Maintains its flexibility, absorbing shocks, vibrations, swelling, shrinking and structural movements
- Tack free in 24-48 hours; cures in 5-7 days without shrinking
- · Ideal for large surfacearea applications requiring long open times







- Fast-cure version of 3M[™] Marine Adhesive Sealant 5200
- Tack free in 1 hour; completely cures within 24 hours
- Ideal for applications requiring a fast, long-term seal, above or below waterline:
- hull to deck seams
- wood to fiberglass
- marine hardware
- hull and stern joints





KEEP YOUR



BOAT AFLOAT



3M[™] Marine Adhesive Sealants

SPECIFICATIONS

Product	Tack-free Time (mins)	Shore A Hardness (ASTM C661)	Elongation at Break % (ASTM D412)	Tensile Strength PSI (ASTM D412)	
3000 UV	40-60	30	>300	145	
4000 UV	15-30	40	>700	500	
4200 FC	50-90	40	>600	0 300	
5200	>48 hours	68	>800	700	
5200 FC	60-120	60	>900	600	
Marine Silicone	5-10	20	>350	220	

ORDERING INFORMATION

Product	Part No.	Container Size	Color	Quantity/Case	Billing UPC
3000 UV	_	290 mL Cartridge	White	12	00-076308-98241-6
	_	290 mL Cartridge	Black	12	00-076308-98242-3
4000 UV	05280	3 oz. Tube	White	6	00-051135-05280-8
	06580	10 oz. Cartridge	White	12	00-051135-06580-8
	06564	10 oz. Cartridge	Black	12	00-051135-06564-8
4200 FC	05260	3 oz. Tube	White	6	00-051135-05260-0
	06560	10 oz. Cartridge	White	12	00-051135-06560-0
	05205	3 oz. Tube	Black	6	00-051135-05205-1
	06504	10 oz. Cartridge	Black	12	00-051135-06504-4
	06502	10 oz. Cartridge	Mahogany	12	00-051135-06502-0
5200	06501	10 oz. Cartridge	Tan	12	00-051135-06501-3
	05206	1 oz. Tube	White	12	00-051135-05206-8
	05203	3 oz. Tube	White	6	00-051135-05203-7
	06500	10 oz. Cartridge	White	12	00-051135-06500-6
	06535	1 oz. Tube	White	12	00-051135-06535-8
5200 FC	05220	3 oz. Tube	White	6	00-051135-05220-4
L	06520	10 oz. Cartridge	White	12	00-051135-06520-4
	08029	1/10 gallon Cartridge	Clear	12	0-00-51135-08029-0
Marine	08019	3 oz. Tube	Clear	6	0-00-51135-08019-1
Silicone	08027	1/10 gallon Cartridge	White	12	0-00-51135-08027-6
	08017	3 oz. Tube	White	6	0-00-51135-08017-7

For more information visit 3M.com/marine.

Warranty, Limited Remedy, and Disclaimer: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. User is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application. Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



3M.com/marine

3M Industrial Adhesives and Tapes Division Building 225-3S-06 St. Paul, MN 55144-1000 1-800-362-3550

3M is a trademark of 3M Company. Please recycle. Printed in USA. © 3M 2016 (Rev. 6/2016). All rights reserved. 78-9236-7267-5