

## Dynaloy specialty chemistries solvent guide

Product use								
Conformal coating removal	Depotting/ decapsulation	3D SLA parts cleaning	Cleaning mixing and metering equipment	Cleaning spray guns, nozzles, tips, etc.	Flushing application/ dispensing equipment	Cleaning molds	Adhesive removal	Description/notes
To remove epoxies								
•	٠		•	•				Removes amine-cured epoxies
•	٠							Removes amine-cured epoxies
•	٠		٠	٠			۰	Removes anhydride-cured epoxies
•	٠		•	•			۰	Removes anhydride-cured epoxies
					•			Removes uncured epoxies
To remove urethanes								
			•	•		•	•	Excellent for cured material
					•			Flushes that leave minimal residue
			•	•		•	•	Excellent for cured material
			•	•			•	Excellent for crystallized isocyanates and cured material
					•			Removes uncured urethane
•	•		•	•		•	•	711 is aluminum-safe
					•			Aggressive flushing solvent
						•		Removes mold releases and residues
		0			•			Versatile flush for uncured materials
			•		•			Removes liquid isocyanate
			•		•			Equipment storage fluid
•								Electronics cleaner
•								Electronics cleaner
•	•		•	•			•	Dissolves at room temperature
•	•		•	•			•	Nonflammable version of 225
					•			Excellent for uncured silicones
•	•		•				•	Essentially noncorrosive
•	٠		•				•	Removes methacrylate adhesives
Dynasolve 699     •     •     •     Removes methacrylate adhesives								
							•	Removes PUR reactive adhesives
	•							Removes polyimides
							•	Citrus-based cleaner
		.         .           .         .	<ul> <li>Contormat coating</li> <li>Contormat coating&lt;</li></ul>	<ul> <li>Contormat coating control transition</li> <li>Cleaning mixing and metering equipment</li> </ul>	•       •	••••••••••••••••••••••••••••••••••••	•••       ••••       •••       •••	·       ·



Eastman Chemical Company Corporate Headquarters P.O. Box 431 Kingsport, TN 37662-5280 U.S.A. U.S.A. and Canada, 800-EASTMAN (800-327-8626) Other Locations, +(1) 423-229-2000

www.eastman.com/locations

Although the information and recommendations set forth herein are presented in good faith, Eastman Chemical Company and its subsidiaries make no representations or warranties as to the completeness or accuracy thereof. You must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and for the health and safety of your employees and purchasers of your products. Nothing contained herein is to be construed as a recommendation to use any product, process, equipment, or formulation in conflict with any patent, and we make no representations or warranties, express or implied, that the use thereof will not infringe any patent. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS AND NOTHING HEREIN WAIVES ANY OF THE SELLER'S CONDITIONS OF SALE.

Safety Data Sheets providing safety precautions that should be observed when handling and storing our products are available online or by request. You should obtain and review available material safety information before handling our products. If any materials mentioned are not our products, appropriate industrial hygiene and other safety precautions recommended by their manufacturers should be observed.

© 2016 Eastman Chemical Company. Eastman brands referenced herein are trademarks of Eastman Chemical Company or one of its subsidiaries or are being used under license. The © symbol denotes registered trademark status in the U.S.; marks may also be registered internationally. Non-Eastman brands referenced herein are trademarks of their respective owners.