

MarksmanELITE

High Resolution InkJet Printing










MarksmanELITE

Dimensions:







Controller Specifications:

Touch Screen Display **Operator Interface**

QWERTY Keypad **Enclosure** Memory

Connectivity Processor **Data Storage Power Input**

Operating System **Auto Codes**

17" Color Touch Screen

Graphical User Interface, WYSIWYG Editor

Sealed Elastomer Stainless Steel

2 GB, 200 pin DDR2 SO-DIMM 4 USB, 2 RS232 Serial Intel® Atom™ N2800 40 GB Solid State SATA drive 100-240VAC, 50-60Hz at 3A max

Windows® Embedded Standard 7 Time, Date, Use By, Julian, Count, User

Defined Shifts, Variable Input

Bar Codes

I2of5, UPC A/E, Code 39, C93, 128,

Data Matrix

Logos **Fonts**

Number of Printheads

Printhead to Controller

Environment

Operating Humidity

Monochrome bit map files only Windows True Type fonts

Up to 4 768 or 384, Max two production lines, heads split in any configuration

Maximum distance between printhead and controller is 25 ft (7.6 meters) max Ambient operating temperature:

40° to 104° F (5° to 40° C) 10-90%, non-condensing

Features and Benefits:



Color Touch Screen – 17" color graphical user interface guides users easily through menu functions.

Designed with fewer components - up to 50% less components than previous models maximizing reliability and uptime.

Less Power - utilizing Intel's low power Atom processor and Solid State Disk the Elite consumes a third less power compared to previous models.

Windows Based - allows for easy user interface and easy message creation.

Optional Keyless message selection allows user to easily select message for print.

Distributor Information:



